

# CMBS080 | DATASHEET

# 45° beam splitter with mount for 116.0 mm claming diameter optics





#### **SPECIFICATIONS**

### **Optical specifications**

Front coating		Beam splitter 50/50 @ 45°, bandwidth 430-670 nm
Back coating		Normal reflectance <0.5%, bandwidth 430-670 nm
Clear aperture	(mm)	108
Deviation angle	(°)	90
Working distance difference <sup>1</sup>	(mm)	137.9

## **Mechanical specifications**

Clamping size	(mm)	116.0
Clamping system		lockring
Length	(mm)	160.9
Width	(mm)	144.0
Height	(mm)	160.9
Mass	(g)	2477

<sup>1</sup> Value to be subctrated from the objective or illuminator working distance when the CMBS is used

## **KEY ADVANTAGES**

Ready to use and easy to setup.

Ideal to create coaxial illumination solutions.


50% transmission and 50% reflection.

Easy and secure clamping system.

Compatible with telecentric lenses and illuminators.

**CMBS series** is a collection of 50/50 plate beam splitter modules designed to create highly efficient coaxial illumination solutions with Opto Engineering® telecentric lenses and collimated illuminators.

#### **CMBS SETUP**



# **COMPATIBLE PRODUCTS**

Full list of compatible products available here.



A wide selection of innovative machine vision components.