



# WI080 | DATASHEET

## Protective window for 116.0mm clamping diameter optics



**WI plates** is a range of optical windows designed to protect telecentric lenses and collimated illuminators.



### SPECIFICATIONS

#### Optical specifications

Transmittance band	(nm)	430-670
Substrate		Borofloat

#### Mechanical specifications

Diameter	(mm)	116.0
Thickness <sup>1</sup>	(mm)	5
Mass	(g)	80

<sup>1</sup> When a WI windows is placed in front of a lens, its working distance increases of approximately 1/3 of the window thickness

<sup>2</sup> CMHO series clamping mechanics may be used prior verification of mechanical compatibility (see CMHO series mechanical drawings on-line). **CMHO is not compatible with the combination of the following: WI + CMWF assembly and TC13xxx**

### COMPATIBILITY <sup>2</sup>

This products is compatible with the following CMWF:

- CMWF080

This products is compatible with the following CMMR:

- CMMR080

### COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.