



OPTO ENGINEERING

ITA50-GC-10C-IP | DATASHEET

Area scan camera 5MP, Sony IMX264, CMOS Global shutter, 2/3", Color, 1 GigE, POE, C mount



KEY ADVANTAGES

IP67-rated housing

Protection against water and dust.

MADE IN ITALY

Cameras designed and manufactured in Italy by Opto Engineering.

TOP QUALITY SERVICE

5 years warranty.

Ruggedized

-25° C to 65° operating temperature. Stainless steel mount, milled aluminum body. Tested for shock and vibration resistance.

MAXIMUM CONNECTIVITY

Isolated PoE supply, broad range of I/Os, serial communication.

HIGH PROCESSING CAPABILITY

Large on-board image buffer, large FPGA.

EXCELLENT QUALITY/PRICE RATIO

GEN*i*CAM

GigE
VISION

1288
EMVA Standard Compliant



ITALA-G.IP series is a series of GigE vision PoE area scan cameras featuring an IP67-rated housing. By adding sealed lens tubes from IPT series and IP67 cables, ITALA G.IP cameras ensure protection against solid particles like dust, dirt, and sand and water.

KEY FEATURES



IP67



1 GIGE



12-24 VOLT



POWER OVER
ETHERNET



12-BIT DEPTH



BURST



IMAGE COM-
PRESSION



FAST
TRIGGER
MODE



DUAL
EXPOSURE




SEQUENCER




PRECISION
TIME
PROTOCOL



SCHEDULED
ACTION
COMMAND



REGION OF
INTEREST



BINNING
AND
DECIMATION



CHUNK DATA



AUTO WHITE
BALANCE




COLOR
CORRECTION
MATRIX




OPTO
ISOLATED I/O



ENCODER



DUAL SERIAL
INTERFACE



MODBUS



API C



API C++



API C#



API Python



WINDOWS



LINUX

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.

SPECIFICATIONS

Sensor Specification

| | |
|----------------------|-------------|
| Megapixel | 5 |
| Resolution | 2464 x 2056 |
| Sensor format | 2/3" |
| Sensor diagonal (mm) | 11.0 |
| Pixel size (μm) | 3.45 |
| Sensor model | IMX264 |
| Sensor type | CMOS |
| Shutter | Global |
| Chroma | Color |

Connectivity

| | |
|--|---|
| Data connector | RJ45 |
| Data interface | 1 GigE |
| I/O connector | 12-pin Hirose |
| I/O interface | 2x opto-isolated input 4x opto-isolated output |
| Serial interface | RS232, RS485 |
| Liquid lens controller | no |
| Encoder interface | yes, incremental |
| Power supply (V) | 12-24, PoE (IEEE 802.3af class 2) |
| Max power consumption ² (W) | 3.6 |

Compliance

| | |
|---------------------|--|
| Standards | GigE Vision 2.2, GenICam, GenTL |
| Client software | ITALA View or other GigE Vision 2.x software |
| Operating systems | 64-bit Windows 10/11 Ubuntu 18.04/20.04/22.04 |
| Shock and vibration | EN 60068-2-27 EN 60068-2-6 EN 60068-2-64 |
| Warranty (years) | 5 |

Mechanical Specifications

| | |
|-----------------|--------------------------------------|
| Mount | C |
| Dimensions (mm) | 54 x 54 x 51.3 |
| Clamping system | 16x M3 threaded holes (on all sides) |
| Mass (g) | 200 |

Camera Specification

| | |
|-------------------------------|--|
| Filter | IR cut |
| Frame rate ¹ (fps) | 23.2 |
| Frame rate burst (fps) | 35.6 |
| Exposure time | 1.08 μs - 10 s |
| ADC resolution (bit) | 10/12 |
| Dynamic range (dB) | 71.3 |
| Gain range (dB) | 0-48 |
| SNR (dB) | 40.1 |
| Image buffer (MB) | 384 |
| Image processing | Binning, decimation, ROI, gamma, black level, LUT, defective pixel correction, white balance, color corection matrix |
| Pixel formats | Mono 8/10/12, RGB8, Bayer GR 8/10p/10Packed/12p/12Packed, YUV 422Packed |
| Chunk data | yes |
| User sets | 3 |
| Timers/Counters | 2/4 |
| Synchronization | Free run, software trigger, hardware trigger, PTP (IEEE 1588) |

Environment

| | |
|---|-----------------------|
| Operating temperature ³ (°C) | -25 - +65 |
| Storage temperature ⁴ (°C) | -10 - +60 |
| Operating relative humidity (%) | 20-80, non condensing |
| IP rating | IP67 |


¹ Color-model's fps are calculated using BayerRG8 pixel format

² Measured with 24V power supply

³ Case temperature, measured on the front part of the camera body


⁴ Ambient temperature

M12 PINOUT




| Pin | Signal |
|-----|--------------|
| 1 | GND |
| 2 | +VIN |
| 3 | Opto OUT 3 |
| 4 | Opto IN 0 |
| 5 | Opto OUT 2 |
| 6 | Opto OUT 0 |
| 7 | Opto REF GND |
| 8 | RS232 RX |
| 9 | RS232 TX |
| 10 | Opto REF V+ |
| 11 | Opto IN 1 |
| 12 | Opto OUT 1 |

SENSOR QUANTUM EFFICIENCY



FILTERS TRANSMISSION



RECOMMENDED ACCESSORIES



Opto-Engineering® offers sealed lens tubes of different diameters to be used with varying lens sizes (IPT-Series) and sealed M12 cables (CB series) to complete your vision system.

COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.