

## High-power LED backlights with integrated driver



### SPECIFICATIONS

#### Lighting specifications

Illumination area height	(mm)	400
Illumination area width	(mm)	400
Number of LEDs		2304
Light color, peak wavelength		IR, 850 nm
Spectral FWHM	(nm)	35
Illuminance, continuous <sup>1</sup>	(klux)	0.01
Irradiance, continuous <sup>1</sup>	(W/m <sup>2</sup> )	57
Illuminance, boosted <sup>1</sup>	(klux)	0.02
Irradiance, boosted <sup>1</sup>	(W/m <sup>2</sup> )	123
Illuminance, strobe <sup>1</sup>	(klux)	0.06
Irradiance, strobe <sup>1</sup>	(W/m <sup>2</sup> )	324
Diffuser		yes
Collimation film		optional

#### Mechanical specifications

Height	(mm)	408.0
Width	(mm)	426.0
Thickness	(mm)	24.0
Mass	(g)	2825
Clamping system		4x M4 threaded holes

#### Environment

Operating temperature	(°C)	0-40
Storage temperature	(°C)	0-50
Operating relative humidity	(%)	20-85, non condensing
Installation		Indoor use only
IP rating		IP54

### KEY ADVANTAGES

#### High-power light output

**Built-in driver** for continuous and strobe operations

#### Industry standard 5 PIN M12 Connector

with PNP/NPN/analog dimming input

#### Optional collimating, polarizing and protective filters

**Compact & robust design** with reduced thickness (24 mm) and thin edges

**Automatic shutdown** in case of overheating

**The LT3BC series** features high-performance LED backlights designed to provide high-power light output, excellent uniformity and contrast thanks to high-efficiency LEDs.

#### Electrical specifications

Operating mode		Continuous and strobe
Supply voltage	(V)	24
Current, continuous	(mA)	3840
Power consumption, continuous	(W)	92
Current, boosted	(mA)	7680
Power consumption, boosted	(W)	184
Peak current, strobe	(mA)	20480
Peak power consumption, strobe	(W)	492
Min pulse duration	(μs)	3
Max pulse duration	(ms)	10
Max duty cycle	(%)	10
Typical pulse delay	(ns)	300
Typical jitter	(ns)	10

I/O interface PNP logic input, NPN logic input, analog dimming input

Connector 2x M12 straight plug male connector


Included cable not included

#### Eye safety

Risk group (CEI EN 62471:2010) Risk group 1

<sup>1</sup> At emitting surface.


## CONNECTOR PINOUT



Pin	Function
1	+24Vdc
2	NPN
3	GND
4	PNP
5	Analogue dimming (0-10V)

## COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

## LED color spectrum

