

Analogue lighting controller unit, 1 channel, 24V, 2A, constant mode, UK power cord, power adaptor 24V plug



Opto Engineering® offers light intensity controllers available as accessories to precisely adjust the light intensity of our wide range of lights.



SPECIFICATIONS

Electrical specifications

| | | |
|--------------------|---------------------|-------|
| Light control type | Analog (knob) | |
| Operating mode | Continuous | |
| Status LEDs | No | |
| Supply voltage | (V) | 24 DC |
| Input | - | |
| Output channels | 1, constant current | |
| Output voltage | (V) | 24 |
| Max output current | (A) | 2 |
| Max output power | (W) | 48 |
| Output | - | |
| Power cord | Included (UK) | |

Mechanical specifications

| | | |
|----------|----------|-----|
| Width | (mm) | 24 |
| Length | (mm) | 55 |
| Height | (mm) | 90 |
| Mass | (g) | 140 |
| Mounting | DIN rail | |

Environment Specification

| | | |
|-----------------------------|-----------------|-----------------------|
| Operating temperature | (°C) | 0-40 |
| Storage temperature | (°C) | 0-50 |
| Operating relative humidity | (%) | 20-85, non condensing |
| IP rating | IP20 | |
| Installation | Indoor use only | |

COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.