



LTRNHCNW | DATASHEET

Ring LED illuminator, inner diameter 4.0mm, straight type, white, 6500 K



KEY ADVANTAGES

Mechanically fitting Opto Engineering® optics

Each lens integrates specific mechanical interfaces.

Specific illumination geometry

Illumination path matches Opto Engineering lenses viewing angle and numerical aperture.

High performance to price ratio

Cost-effective, without quality compromises.

LTRNST series are LED ring illuminators specifically designed for a wide range of Opto Engineering products. Specifically, the LTRNHCNW model perfectly fits Opto Engineering® HCN lenses.

SPECIFICATIONS

Lighting specifications

Illumination area outer diameter	(mm)	10.0
Illumination area inner diameter	(mm)	4.0
Optimal working distance (min-max)	(mm)	2-30
Number of LED rows		1
Emission angle	(°)	0
Light color, peak wavelength		white, 6500 K
Illuminance at min WD ¹	(lux)	487000
Illuminance at max WD ¹	(lux)	21500

Electrical specifications

Supply voltage ²	(V)	24
Current	(mA)	110
Power consumption	(W)	2.6
Estimated MTBF ³	(hours)	-
Max pulse voltage ⁴	(V)	16
Max pulse current ⁵	(mA)	2400
Max duty cycle	(%)	1
Max pulse duration	(ms)	1
Connector ⁶		Flying leads
Cable length	(mm)	450

Mechanical specifications

Outer diameter	(mm)	37.0
Inner diameter	(mm)	4.0
Height	(mm)	22.0
Mass	(g)	33

Environment


Operating temperature	(°C)	0-45
Operating humidity	(%)	20-85, non condensing

Eye safety

Risk group (CEI EN 62471:2010)	Risk group 1
--------------------------------	--------------

- ¹ ±15%.
- ² Tolerance ±2%.
- ³ At 25°C.
- ⁴ Constant voltage power supply.
- ⁵ Constant current power supply.
- ⁶ Red Cable is V+, white cable is V-.

LED color spectrum



COMPATIBLE PRODUCTS

Full list of compatible products available [here](#).



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.

ILLUMINATOR CONNECTION

