

FTBP660M35.5 | DATASHEET

Optical filter, band pass, dark red



KEY ADVANTAGES

High and precise transmission Wide range selection Available for fixed focal length lenses and telecentric lenses Increase resolution Block unwanted light Tolerate high temperature environment

Light filtering is a typical need in machine vision applications. Together with LED illuminators, filters can improve image contrast by blocking unwanted light and increase the accuracy and repeatability of the vision system.

SPECIFICATIONS


Optical specifications band pass Туре Light color dark red Wavelength range¹ (nm) 640 - 695 Cut-on 50% transmission (nm) -Cut-off 50% transmission (nm) -FWHM² (nm) 55

Mechanical specifications

Filter Thread		M35.5 x 0.5
Outer Diametere	(mm)	38.5
Clear Aperture	(mm)	30.5
¹ Peak transmission >90%		

² Telerance $\pm 10 \text{ pm}$

² Tolerance $\pm 10 \text{ nm}$



COMPATIBLE PRODUCTS

Full list of compatible products available here.



A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.