

FTLP510TC | DATASHEET

Optical filter, long pass, yellow



KEY ADVANTAGES

High and precise transmission Wide range selection Available for fixed focal length lenses and telecentric lenses Increase resolution Block unwanted light Tolerate high temperature environment

Light filtering is a typical need in machine vision applications. Together with LED illuminators, filters can improve image contrast by blocking unwanted light and increase the accuracy and repeatability of the vision system.

SPECIFICATIONS

Optical specifications

Туре		long pass
Light color		yellow
Wavelength range ¹	(nm)	515 - 1100
Cut-on 50% transmission	(nm)	515
Cut-off 50% transmission	(nm)	-
FWHM ²	(nm)	-


Mechanical specifications

Filter Thread		TC insert
Outer Diametere	(mm)	24.5
Clear Aperture	(mm)	15.0
¹ Peak transmission >90%		

² Tolerance $\pm 10 \text{ nm}$

ADDITIONAL NOTE

Filter not compatible with TC23004, TC23007, TC23009 and TC23012. For other telecentric lens some vignetting may occur, depending on sensor size.



500

600

Wavelength [nm]

700

800

COMPATIBLE PRODUCTS

Full list of compatible products available here.

OPTICS
LIGHTING
CAMERAS
SOFTWARE
ACCESSORIES

Image: Comparison of the second sec

A wide selection of innovative machine vision components.

All product specifications and data are subject to change without notice to improve reliability, functionality, design or other. Photos and pictures are for illustration purposes only. Data are reported by design, actual lens performance may vary due to manufacturing tolerances.

Fransmission [%]

0

300

400